



SIWT 450

- Custom PLC Controlled with Data Logger
- 0.01 to 0.1 ppm Silver Ion

Model No.	SIWT 450A50T	SIWT 450A80T	SIWT 450A50M	SIWT 450A80M
Pipe Size	2" Triclover	3" Triclover	2" BSM	3" BSM
Flow Rate	70 - 450 L/m			
Ag ⁺	✓	✓	✓	✓
Cu ⁺				
Flow Sensor	Insertion flow sensor with stainless steel fitting (Wetted parts materials Fitting)			
Voltage	110 or 240V AC			
Input Voltage	22 ~ 26 VDC			
Output Voltage	22 ~26 Volts			
Water Usage	8,392,800 Litre ~ 41,964,000 Litre (This is highly dependant on water quality)			

Model No.	SIWT 450C50T	SIWT 450C80T	SIWT 450C50M	SIWT 450C80M
Pipe Size	2" Triclover	3" Triclover	2" BSM	3" BSM
Flow Rate	70 - 450 L/m			
Ag ⁺	✓	✓	✓	✓
Cu ⁺	✓	✓	✓	✓
Flow Sensor	Insertion flow sensor with stainless steel fitting (Wetted parts materials Fitting)			
Voltage	110 or 240V AC			
Input Voltage	22 ~ 26 VDC			
Output Voltage	22 ~26 Volts			
Water Usage	8,392,800 Litre ~ 41,964,000 Litre (This is highly dependant on water quality)			



SILVER ION WATER TECHNOLOGY

TEL: +61 3 9701 7089 Email: sales@akwa-solutions.com
 FAX: +61 3 9701 3243 www.akwa-solutions.com