



SIWT 450

Antibacterial Water

- Custom PLC Controlled
- 0.01 to 0.1 ppm Silver

Model No.	SIWT 450A50T	SIWT 450A80T
Pipe Size	2" Triclover	3" Triclover
Flow Rate	23 ~ 375 L/min	90 ~ 750 L/min
Ag ⁺	✓	✓
Cu ⁺		
Flow Sensor	Stainless Steel	Stainless Steel
Power	110 or 240V AC 72 Watts	
Output Voltage	max. 24V DC	
Water Usage	8,392,800 Litre ~ 41,964,000 Litre (This is highly dependant on water quality)	

Model No.	SIWT 450C50T	SIWT 450C80T
Pipe Size	2" Triclover	3" Triclover
Flow Rate	23 ~ 375 L/min	90 ~ 750 L/min
Ag ⁺	✓	✓
Cu ⁺	✓	✓
Flow Sensor	Stainless Steel	Stainless Steel
Power	110 or 240V AC 72 Watts	
Output Voltage	max. 24V DC	
Water Usage	8,392,800 Litre ~ 41,964,000 Litre (This is highly dependant on water quality)	



SILVER ION WATER TECHNOLOGY

TEL: +61 3 9701 7089 Email: sales@akwa-solutions.com
www.akwa-solutions.com